

Excavators / E55 Compact Excavator

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat E55

⊖ Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,200 rpm
Horsepower	36.4 kW
Turbocharged Engine	■

⊖ Performance

Operating Weight	5585 kg
Weight Class	5.6 t
Travel Speed - High	5 km/h
Travel Speed - Low	3.1 km/h
Arm Digging Force	25,580 N
Bucket Digging Force	39,930 N
Boom Swing - Left	75°
Boom Swing - Right	50°
Maximum Dig Depth	3.9 m
Max Dump Height	4.1 m
Maximum Reach at Ground Level	6.1 m

⊖ Capacities

Fuel Tank	79,9 l
------------------	--------

⊖ Hydraulic System

Auxiliary Std Flow	75,7 l/min
Auxiliary Pressure	210 bar

⊖ Dimansion

Length	5243 mm
Overall Length in Travel Position	5243 mm
Width	1960 mm / 2060 mm
Height	2541 mm

⊖ Features

Cab Enclosure	■
Cab Heater	■
Cab Air Conditioning	<input checked="" type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Conventional
Engine Shutdown	■
Auxiliary Hydraulics	■
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Quick Tach System	<input checked="" type="checkbox"/>
Rubber Track	■
Selectable Auxiliary Hydraulic Flow	■
Angle Blade	<input checked="" type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.