



# IQ LIFT PRO 10

The IQ LIFT PRO 10 push around lift is designed to provide the safest access solution for working at height.

This push around lift has been designed specifically for low-level access and can withstand the demands of everyday use on site while offering enhanced safety for the user. Through years of development the IQ LIFT PRO 10 leads the industry in safety with a sophisticated control unit that monitors the lift's performance.

The IQ LIFT PRO 10 can reach a platform height of 3M with a platform base 1.04 x 0.52, along with the built in tool tray, the IQ LIFT PRO 10 can hold 240KG of weight which allows of 1 person + their tools and still reach its maximum working height. The lift will take 18 seconds to fully extend and 20 seconds to descend. For emergency use the emergency release lever located at the back of the machine on the base unit for a controlled decent. User manual can be found attached to the side of the lift. This lift is equipped with two emergency stop switches, one at the platform control and one at the base control, that when activated, will render the unit inoperable until reset.

Without charging the IQ LIFT PRO 10 battery life can last average 3 days on average use but is recommended that if regularly used to recharge at the end of every job.

**MAX WORKING HEIGHT** 5M

**STOWED HEIGHT** 1.75M

**GROSS WEIGHT** 394KG

[HIRE PRODUCT](#)

[BUY PRODUCT](#)

+44(0) 1244 833 933

sales@popupproducts.co.uk

popupproducts.co.uk



## KEY FEATURES

- ✓ LEADING EDGE SAFETY
- ✓ INTELLIGENT FEEDBACK
- ✓ QUICK & SMOOTH ELEVATION
- ✓ LOW COST OF OWNERSHIP
- ✓ ENVIRONMENTALLY FRIENDLY
- ✓ MANOEUVRABLE
- ✓ LONG BATTERY LIFE
- ✓ 2 YEAR PARTS WARRANTY
- ✓ EN 280 & UK CA CERTIFIED

# PRODUCT DIMENSIONS

## DIMENSIONS

PRODUCT CODE	IQPRO10
MAX WORKING HEIGHT (M)	4.95
MAX PLATFORM HEIGHT (M)	2.97
PLATFORM CAPACITY SWL (KG)	240
OVERALL WIDTH (M)	0.76
OVERALL LENGTH (M)	1.31
STOWED HEIGHT (M)	1.75
PLATFORM SIZE (M)	1.04(L) X 0.52(W)
GROSS WEIGHT (M)	394
MAX WIND SPEED (M/S)	0
RAISE/LOWER TIME (SEC)	18/2012
POWER SOURCE (M)	12 VOLT DC BATTERY
CHARGER (M)	

BUILT IN MULTI-VOLTAGE (90V-240V).  
110V SOCKET FITTED AS STANDARD



FULL LENGTH SPRING  
LOADED SWING GATES



ANTI-SURF  
AUTO BRAKING



360 GUARD  
RAIL



USB CHARGER  
PORT



TOOL TRAY &  
ODDMENTS BIN



CONTROL  
PANEL